

## CLAIMS

What is claimed as being new and desired to be protected by  
LETTERS PATENT of the United States is as follows:

*Shaffer* 1. A sure grip screwdriver system for allowing a user to  
screw and unscrew threaded fasteners in a convenient and  
efficient manner comprising, in combination:

a shaft fabricated of a rigid metallic material in a  
cylindrical configuration with an axis and having a handle end  
and a working end, the shaft having a working inner portion  
adjacent to the handle end and a working outer portion adjacent  
to the working end and with a flat cut face on the outermost  
extent of the working end perpendicular to the axis of the shaft,  
the working outer portion having a generally cube-shaped  
configuration with a square cross section and an axial length of  
a first smaller size adjacent to the face, the working inner  
portion having a generally cube-shaped configuration with a  
square cross section and an axial length of a second larger size  
adjacent to the working outer portion, with a bevel adjacent to  
the working inner portion remote from the face;

a screwdriver handle having a shaft end and a gripping  
surface end, the shaft end having a generally cylindrical recess  
to securely receive and retain in one position the handle end of  
the shaft and with the gripping surface end having a plurality of

axial indentations to facilitate the user's grip of the system; and

a threaded fastener having a threaded portion and a head portion, the threaded portion having threads for coupling to a recipient surface upon rotation and with the head portion having a cylindrical configuration with a central stepped recess, the stepped recess having a cube-shaped interior reception area and an exterior cube-shaped reception area with the interior reception area being smaller to snugly receive the working outer portion of the shaft and with the exterior reception area being larger to snugly receive the working inner portion of the shaft and alternatively, wherein the threaded fastener is of a smaller size, the working outer portion is snugly receivable by the working outer portion and, alternatively, wherein the working portions are of a larger size, the working outer portion is snugly receivable by the working outer portion.

2. A sure grip screwdriver system comprising:

a shaft having a handle end and a working end, the shaft having a working inner portion adjacent to the handle end and a working outer portion adjacent to the working end, the working outer portion having a generally cube-shaped configuration of a first smaller size, the working inner portion having a generally cube-shaped configuration of a second larger size; and

a shaft support with a recess at one end to receive the handle end of the shaft.

3. The system as set forth in claim 2 and further including:

a threaded fastener having a threaded portion and a head portion, the head portion having a cylindrical configuration with a central stepped recess, the stepped recess having a cube-shaped interior reception area and an exterior cube-shaped reception area with the interior reception area being smaller to snugly receive the working outer portion of the shaft and with the exterior reception area being larger to snugly receive the working inner portion of the shaft.

4. The system as set forth in claim 2 wherein the shaft is a kit with a plurality of shafts with each shaft having different sized working portions.

5. The system as set forth in claim 2 wherein the shaft has opposed ends with working surfaces at each end and with a central section having a square cross-sectional configuration for being received by the shaft support.

6. The system as set forth in claim 2 wherein the shaft is a kit with a plurality of shafts with each shaft having different sized working portions and wherein the shaft support is a power tool.